

Setex is the premium hose from SVEBAB. It has been tested and approved to Swedish standard SS2840 and is DNV marked in diameters 38, 51, 63, 76 and 110 mm. The 25 mm hose is type-tested and approved to SS2840/38 mm. The 42 mm hose is P marked according to SPC039.

Setex has a strong jacket construction made of 100% high quality polyester threads, and an inner tube made of 100% EPDM rubber. They are fixed to each other by means of a special rubber layer which penetrates the web structure in a vulcanisation process. This structure leaves an extremely smooth inner surface, keeping pressure losses to an absolute minimum. It also creates a hose with very high resistance to abrasion, chemicals and ozone.

Setex is also produced as a signal hose. This kind of hose has a fluorescent yellow or orange colour. The bright colours clearly mark out the path of the hose and avoid unnecessary confusion between smoke diving hoses and other hoses.

Setex is also available as SETEX HP in diameter 42 mm, and SETEX Extra in diameters 63 mm and 76 mm.

Nominal diam mm	Approx. weight kg/m	Working pressure bar	Burst pressure bar	Abrasion resistance method SS2840: – Double strokes	Verified by coupling – Cycles	Certified/ bar	type approved to
25	0.11	15	100	40	10	22.5	SS2840/38
38	0.21	15	70	100	10	22.5	DNV/SS2840
42	0.25	15	65	150	10	22.5	P marked/SPCR039
42*	0.31	20	100	250	10	30	
51	0.29	15	50	120	10	22.5	DNV/SS2840
63	0.38	15	50	180	10	22.5	DNV/SS2840
63**	0.44	20	75	270	10	30	SS2840
76	0.48	15	50	200	10	22.5	DNV/SS2840
76***	0.57	20	70	300	10	30	
110	0.78	12	45	200	10	18	DNV/SS2840



*42 mm SETEX HP:
Higher burst pressure and abrasion resistance.

**63 mm SETEX EXTRA:
Higher burst pressure and abrasion resistance.

***76 mm SETEX EXTRA:
Higher burst pressure and abrasion resistance.

Another dimensions/colours available on request. The hose can be supplied in lengths up to 1000 metres.

– Part of your personal protective equipment