



NEO
LEADER Fan
EASY POW'AIR
 TECHNOLOGY

PETROL-DRIVEN FAN MT225

A very **concentrated and ultra-powerful** jet of air due to an optimal combination of:

- ▶ A high-strength propeller matched to the power of the engine
- ▶ A red double-layer monobloc shroud made of reinforced high-density polyethylene
- ▶ A high-tech composite grille

Positioning from 0.90 m to 6 m in front of a door without loss of power for:

- ▶ more space to move about
- ▶ less noise inside the building

Precise tilt adjustment

from -10° to +20° with indicator for optimization of direction of air stream up entrance steps or down into a semi-basement

Protective frame

with grey epoxy coating

Compact for easy storage in vehicle trunks

Characteristics

| Model | MT225 NEO |
|--------------------------------|---|
| Reference | I60.10.054N |
| Open air flow | 37 700 m ³ /h |
| PPV air flow according to AMCA | - |
| Weight (dry) | 26,8 kg |
| Dimensions L x H x D | 550 x 568 x 436 mm |
| Propeller diameter | 420 mm |
| Run time at full speed | 1h40 |
| Engine | HONDA GX 120 engine (4-stroke) Automatic engine cutout if oil runs out. Assembly inspected and approved by Honda Motor Co., Ltd |
| Engine power | 3,6 HP according to standard SAE J1349 of 2007 |
| Noise level | 94,8 dB at 3 m |
| Ventilation type | PPV blowing |
| Application | Single door, e.g. house, small apartment block |

Optional accessories:

| | |
|--|------------|
| Mister without coupling (products with coupling: see p. 52) | Consult us |
| High expansion foam adapter without coupling delivered with 35m of polyane plastic film duct (products with coupling: see p. 52) | I60.20.105 |
| 5m ventilation duct | I60.20.147 |
| Adapter for connecting ventilation duct to fan | I60.20.149 |

Ventilation tactics in the catalogue or at www.leader-group.eu
 Freely downloadable interactive ventilation courses at www.leadereducexpert.com
 As part of our policy of constant research to improve our products, we reserve the right to modify our products' characteristics at any time without notice

